

WHAT IS CLAIMED IS:

1. A slippage-preventing device for tubular jack handle comprising:
a jack handle stand having an insertion hole for receiving a
5 tubular handle, said tubular handle being provided with a
locking groove at a front end thereof; and
a movable bar which extends into an inner wall of said
insertion hole through an opening;
said tubular handle pushing aside said movable bar as being
10 inserted into said insertion hole, said movable bar being
resiliently driven back into said insertion hole to lock said
tubular handle at said locking groove.
2. The slippage-preventing device for tubular jack handle of
Claim 1, wherein said tubular handle is provided with an
15 angled-rim tip at said front end thereof, and said movable bar
is provided with a corresponding angled-rim tip at an front end
thereof.
3. The slippage-preventing device for tubular jack handle of
Claim 2, wherein angled rims around respectively said
20 angled-rim tip of said tubular handle and said angled-rim tip
of said movable bar take the shape of a ring.
4. The slippage-preventing device for tubular jack handle of
Claim 1, wherein said jack handle stand includes a bar stand
mounted on an outer wall of said jack handle stand and
25 connecting to said opening on said inner wall of said insertion
hole.

5. The slippage-preventing device for tubular jack handle of Claim 4, wherein said bar stand is solidly screwed onto said jack handle stand.
6. The slippage-preventing device for tubular jack handle of Claim 4, wherein said bar stand is integrally formed on said jack handle stand.
7. The slippage-preventing device for tubular jack handle of Claim 1, wherein an outer end of said movable bar connects with a knob cover and an inner end of said movable bar is provided with a blocking piece, said movable bar firstly being inserted a spring, then passing through said opening of said insertion hole, and connecting with said knob cover.
8. The slippage-preventing device for tubular jack handle of Claim 1, wherein said locking groove of said tubular handle takes the shape of a ring.